

GP1426, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy
Catalog # [GP1426](#)

Mechanical Grounding Connector, 2 Cables to Rod or Pipe, 4 AWG (Sol.) - 2/0 AWG (Str.), 1/2" - 3/4" Pipe, 7/8" - 1" Rod, 3/8" Stud.

Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining A Range Of Parallel Copper Cables Perpendicular To Rod, Pipe Or Column, Direct Burial In Earth Or Concrete

General

Catalog Number	GP1426
EU RoHS Indicator	Yes
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Copper Alloy
Material Type - Screw	DURIUM™ Silicon Bronze
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Type	GP
U Bolt Type	249
UPC	781810260586
UPC 12 Digit	7818102605866

Dimensions

Bolt Size	3/8 in
Dimension - B Length inch	1.50 in
Dimension - Height mm	76.2 mm
Dimension - L Length Overall mm	43 mm
Dimension - Length Overall inch	1.69 in
Dimension - Width fraction	2-3/8 in



Dimension - Width inch	2.38 in
Dimension - Width mm	60 mm

Conductor Related

Conductor - Rod Size	1 in
Conductor Size	#4 AWG Sol - 2/0 AWG Str

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

Product Assets

- [3D Models - GP1426_MODEL-PDF](#)
- [3D Models - GP1426_MODEL-STEP](#)
- [3D Models - GP1426_MODEL-IGES](#)
- [Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_gpla](#)
- [Sales Drawings - SD..013778-01](#)
- [Specifications - GP1426](#)