



# HSB200H12PF2, Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, 250-500 kcmil, 1000 V, 12.00" L, Flame Retardant.



By Burndy  
Catalog # [HSB200H12PF2](#)

Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, 250-500 kcmil, 600 V, 12.00" L, Flame Retardant.

### Application

For Direct Burial

### General

Catalog Number	HSB200H12PF2
Connector Type	HEAVY WALL TUBES
EU RoHS Indicator	Yes
Material	Cross-linked Polyolefin
Sub Brand	HEAT SHRINK
Type	HS-H-PF, Heavy Wall, Flame Retardant
UPC	781810214879

### Conductor Related

Conductor Range	250-500 Kcmil
Conductor Size	250kcmil - 500kcmil

### Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

### Logistics

Carton Quantity	20
Number of Pieces in Package	2

### Product Assets

- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR\\_HSB35H6PF25\\_LineArt](#)
- [Sales Drawings - SD211942-01](#)
- [Specifications - HSB200H12PF2](#)
- [Video - Heat Shrink Product Overview & Installation](#)