



HSB200H12PF2, Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, 250-500 kcmil, 1000 V, 12.00" L, Flame Retardant.



By Burndy
Catalog # [HSB200H12PF2](#)

Heavy Wall Cross-Linked Polyolefin Heat Shrink Tubing, 250-500 kcmil, 1000 V, 12.00" L, Flame Retardant.

Features

- Heavy Wall Heat Shrink Tubing
- Shrink Ratio 3:1
- Inside diameter is coated with adhesive sealant to protect against moisture and corrosion

Application

For Direct Burial

General

Catalog Number	HSB200H12PF2
Connector Type	HEAVY WALL TUBES
EU RoHS Indicator	Yes
Material	Cross-linked Polyolefin
Sub Brand	HEAT SHRINK
Type	HS-H-PF, Heavy Wall, Flame Retardant
UPC	781810214879

Conductor Related

Conductor Range	250-500 Kcmil
Conductor Size	250kcmil - 500kcmil

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	20
Number of Pieces in Package	2

Product Assets

- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR_HSB35H6PF25_LineArt](#)
- [Sales Drawings - SD211942-01](#)
- [Specifications - HSB200H12PF2](#)
- [Video - Heat Shrink Product Overview & Installation](#)