

KC28B1, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy Catalog # KC28B1

Mechanical Grounding Connector, Cable to Flat, 1-4/0 AWG, 5/8" Stud, 1-3/4" Height, B=1-1/4"

Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

KC28B1

General

Catalog Number

| EU RoHS Indicator | Yes |
|-------------------------------|--------------------|
| Material | Copper Alloy, Cast |
| Plated | N |
| Plating Type | Unplated |
| Stud Installation Torque inch | 660 LBS/in |
| pounds | |
| Sub Brand | SERVIT POST |
| Trade Name | SERVIT POST™ |
| Туре | KC and K2C Series |
| UPC | 781810256404 |
| UPC 12 Digit | 7818102564044 |

Dimensions

| Dimension - B Length fraction | 1-1/4 in |
|--------------------------------|----------|
| Dimension - B Length inch | 1.25 in |
| Dimension - Body Width inch | 1.18 in |
| Dimension - Bolt Size fraction | 5/8 |
| Dimension - D inch | 1.50 in |
| Dimension - Height fraction | 1-3/4 |
| Dimension - Height inch | 1.94 in |
| Dimension - Height mm | 49.3 mm |
| Dimension - L Length Overall | 88 mm |
| mm | |
| Dimension - Length Overall | 3.45 in |
| inch | |
| Dimension - Nut Width inch | 1.35 in |
| Dimension - P inch | 0.55 in |
| Dimension - Threads per inch | 11 |
| | |



Conductor Related

Total

Conductor - Copper Solid Size 1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG

Conductor - Copper Solid Size 1 AWG-4/0 AWG

Range Conductor - Copper Str Size 1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG

Conductor - Copper Str Size 1 AWG-4/0 AWG

Range Physical Attribute - Number of 1 Conductors Accommodated

Certifications And Compliance

| Certification - CSA Approved | No |
|----------------------------------|-------|
| Certification - ETL | No |
| Certification - UL Listed Direct | Yes |
| Burial | |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL467 |
| Standards - Industry Standards | UL467 |
| Met | |
| Standards - RoHS Compliance | EX |
| Status | |
| UL Listed | Yes |
| | |

Product Assets

3D Models - KC28B1_MODEL-STEP
3D Models - KC28B1_MODEL-IGES
3D Models - KC28B1_MODEL-PDF
Catalogs - BURNDY Master Catalog - Section E2 - Mechanical
Grounding
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_KC_Lineart
Sales Drawings - SD..055917
Specifications - BURNDY_KC28B1_Specsheet
Specifications - KC28B1

