

PENA13GAL, Oxide Inhibitor, Gallon Container

By Burndy Catalog # PENA13GAL

Oxide Inhibiting Electrical Joint Compound, 1 Gallon, For Al-Al, Al-Cu & Al Conduit Threads / Insulated Cable.

Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

For Aluminum To Copper, Aluminum To Aluminum, Aluminum To Conduit

General

Application - For Use On Aluminum to

Aluminum; Aluminum to Conduit; Aluminum to Copper

Catalog Number PENA13GAL

Container Type Can
EU RoHS Indicator Yes
Pour Point -40 °F
Sub Brand PENETROX
Temperature - Dropping Point 350 °F

Fahrenheit



Trade Name PENETROX™

Type A13

UPC 781810593028 UPC 12 Digit 7818105930288

Viscosity at 100 Fahrenheit 250 °F

Certifications And Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Container Size 1 Gallon

Product Assets

Catalogs - BURNDY Master Catalog - Section F - Accessories Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_PENA13QT_LineArt

Sales Drawings - 50016093

SDS - PENETROX A-13 FRENCH SDS

SDS - PENETROX A-13 SDS

SDS - PENETROX A-13 ESPANOL SDS

SDS - PENETROX A-13 GERMAN SDS

SDS - PENETROX A-13 ITALIAN SDS

SDS - PENETROX A-13 PORTUGUESE SDS

Specifications - PENA13GAL