

TP1014, Vinyl Ring Terminal For 12 - 10 AWG

By Burndy
Catalog # [TP1014](#)



Copper Terminal, Ring Tongue, 12-10 AWG, 1/4" Stud, Vinyl Insulated, Tin Plated, Wire strip Length: 19/64".

Features

- Expanded insulation support accepts standard and large wire diameters providing lower inventory requirements and greater flexibility
- Funnel entry for easy wire insertion
- Manufactured of pure electrolytic copper to provide maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Deep V groove serrations in the inner barrel provides added holding strength and better conductivity

Application

For Commercial And Light Duty Industrial Control And Power Circuit Applications

General

| | |
|--------------------------------------|---------------|
| Catalog Number | TP1014 |
| Color Code | Yellow |
| Connector Type | Ring Terminal |
| EU RoHS Indicator | Yes |
| Feature - Barrel Style | Shrouded |
| Insulation | Y |
| Insulation Type | Vinyl |
| Material | Copper |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Tongue Type | Ring |
| Plated | Y |
| Plating Type | Tin |
| Sub Brand | VINYLUG |
| Trade Name | VINYLUG™ |
| Type | Ring Tongue |
| UPC | 781810711040 |
| UPC 12 Digit | 7818107110400 |

Dimensions

| | |
|-----------------------------------|---------|
| Cable Insulation Diameter Maximum | 0.28 in |
| Dimension - Bolt Size fraction | 1/4 |
| Dimension - Hole Size fraction | 10/37 |
| Dimension - Hole Size inch | 0.27 in |

| | |
|---------------------------------|----------|
| Dimension - L Length Overall mm | 32 mm |
| Dimension - Length Overall inch | 1.26 in |
| Dimension - Pad Width inch | 0.53 in |
| Dimension - Strip Length inch | 19/64 in |
| Dimension - Stud Size inch | 1/4 in |
| Dimension - Z (inch) | 0.40 in |

Electrical Ratings

| | |
|-------------------|-------|
| Voltage - Maximum | 600 V |
|-------------------|-------|

Conductor Related

| | |
|-----------------|--------------------|
| Conductor Range | #12 AWG to #10 AWG |
| Conductor Size | 12 - 10 AWG |
| Conductor Type | CU C Str-Size |

Certifications And Compliance

| | |
|------------------------------------|-------|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL467 |
| Standards - Industry Standards Met | UL467 |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------|-------|
| Carton Quantity | 600 |
| Pallet Quantity | 99999 |

Product Assets

[3D Models - TP1014_MODEL-IGES](#)
[3D Models - TP1014_MODEL-STEP](#)
[3D Models - TP1014_MODEL-PDF](#)
[Catalogs - BURNDY Master Catalog - Section B - Small Compression](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)



A Hubbell brand