

YPC33R26U, Figure 6-shaped Connector

By Burndy
Catalog # YPC33R26U



Figure 6 shape connector separates run and tap wires and minimizes galvanic corrosion of conductors, Run, Al and Cu:250 (37) - 400 (37).

Features

- Extra wide range universal compression connector
- Figure 6-shape separates run and tap wires minimizes galvanic corrosion of conductors
- Connector can be gripped in tool and slipped over line for easy installation
- Pre-filled with PENETROX joint compound and stripealed

Application

For Combinations Of Copper, Aluminum, ACSR, 6201, 5005 And Compressed And Compact Conductors

General

Catalog Number	YPC33R26U
Die Index	N
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Sub Brand	CRIMPIT
Trade Name	CRIMPIT™
Type	YPC-U
UPC	781810137505
UPC 12 Digit	7818101375055

Dimensions

Dimension - Height inch	2.28 in
Dimension - L Length Overall mm	54 mm
Dimension - Length Overall inch	2.125 in
Dimension - Width inch	1.16 in

Conductor Related

Conductor - ACSR Str Run Range	266.8 kcmil-397.5 kcmil
Conductor - ACSR Str Tap Range	6 AWG- 1/0 AWG
Conductor - AL Str Run	250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397

Conductor - AL Str Run Range	kcmil;400 kcmil
Conductor - AL Str Tap	250 kcmil-400 kcmil
Conductor - AL Str Tap Range	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Str Run	6 AWG-2/0 AWG
Conductor - Copper Str Run Range	250 kcmil;300 kcmil;350 kcmil;400 kcmil
Conductor - Copper Str Tap	250 kcmil-400 kcmil
Conductor - Copper Str Tap Range	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Str Tap Range	6 AWG-2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Run • CU C Str-Run • CU C Solid-Run • ACSR C Str-Run • AL C Str-Tap • CU C Str-Tap • CU C Solid-Tap • ACSR C Str-Tap

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Product Assets

- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YPCAU_Lineart](#)
- [Sales Drawings - sd051577-01](#)
- [Specifications - YPC33R26U](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
BRDY_MX-YPC33R26U-SPEC-EN | REV 10/2024