BRYANT®

Locking Devices, Bryant Power Interrupting, Industrial, Receptacle, 30A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

By Bryant
Catalog # 20403

Locking Devices, Bryant Power Interrupting, Industrial, Single Receptacle,30A 600V AC/ 20A 250V DC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black, For F.S. and F.D. boxes

Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Thermoset molded housing provides maximum heat resistance

Application

Extra Heavy Duty Industrial Specification Grade

General

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	20A/30A Single Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Bryant
Style	Grounding
Type	Receptacle
UPC	781786618473

Dimensions

Dimensions	3.28 in x 1.94 in x 1.75 in
Display Size	Standard Sized Product
Height	1.75 in
Length	3.28 in
Width	1.94 in

Electrical Ratings

Amperage Rating	20A/30 A
Connectivity	Terminal Screws
Current Rating	20A/30 A
Phase	Single Phase
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

Conductor Related

Number Of Wires	4-Wire
Wire Size	#14 AWG to #10 AWG

Logistics

Carton Quantity	20

Product Assets

Catalog Page - Bryant H-25 Catalog page
Catalogs - Bryant Full Line Catalog

Related Products

20405 - Wallplates and Boxes, Weatherproof Covers, 1- Gang, For 30A Power Interrupting, Standard Size, Cast Aluminum, New Style

20406 - Wallplates and Boxes, Non-Weatherproof Covers, 1-Gang, For 30A Power Interrupting, Standard Size, Cast Aluminum

21415 - Locking Devices, Bryant Power Interrupting, Industrial, Male Plug, 30A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal and White