BRYANT®

Straight Blade Devices, Receptacles, Hospital Grade QUADPLEX Receptacle, Surge Suppression, Isolated Ground, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R



By Bryant
Catalog # 21254HSIA

Straight Blade Devices, Receptacles, Hospital Grade QUADPLEX Receptacle, Surge Suppression, Isolated Ground, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Ivory

Features

- Hospital Grade QUADPLEX Receptacle
- Surge Suppression
- Isolated Ground
- 20A 125V
- 2-Pole 3-Wire Grounding

Application

Quad-Plex

General

Catalog Number	21254HSIA
Color	Ivory
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Visual Status Indicator
Item Type	Smooth Face
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Outlets	4
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Bryant
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Hospital Grade
Type	Four Outlet Receptacle
UPC	781786190290

Dimensions

Dimensions	4.3 in x 4.30 in x 0.92 in
Display Size	Standard Sized Product
Height	0.92 in
Length	4.3 in
Weight	0.35 lb
Width	4.3 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current / Amperage Rating	20 A
Current Rating	20 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	2500 W

Conductor Related

Number Of Wires	3-Wire

Certifications And Compliance

Nema Rating	5-20R

Logistics

Carton Quantity	10

Product Assets

Catalog Page - BRY D-3 Catalog Page
Catalog Page - BRY B-5 Catalog Page
Catalog Page - BRY A-6 Catalog Page
Catalogs - Bryant Full Line Catalog
Literature - General Literature - Healthcare Solutions
Literature - General Literature - Surge Protection Devices
Specifications - 21254HSIA

©2024 Hubbell Incorporated. All rights reserved