



Locking Devices, Bryant Power Interrupting, Industrial, Flanged Receptacle, 30A 250V DC/600V AC, Non-NEMA, Screw Terminal, Cast Aluminum

By Bryant
Catalog # 21420



Locking Devices, Bryant Power Interrupting, Industrial, Flanged Receptacle, 30A 600V AC/20A 250V DC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Cast aluminum angle housing with 3/4 in. NPT hub

Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Angled housing reduces the profile of the device and makes mating and un-mating easier
- Metallic weather protective spring loaded cover provides protection from moisture and dust

Application

Extra Heavy Duty Industrial Specification Grade

General

Color	Metallic
Environmental Conditions	IP44 Suitability
Item Type	20A/30A Angled Single Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Bryant
Style	Grounding
Type	Flanged Receptacle
UPC	781786618633

Dimensions

Dimensions	3.28 in x 1.94 in x 1.75 in
Display Size	Standard Sized Product
Height	1.75 in
Length	3.28 in
Width	1.94 in

Electrical Ratings

Amperage Rating	20A/30 A
Connectivity	Terminal Screws
Current Rating	20A/30 A
Phase	Single Phase
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

Conductor Related

Number Of Wires	4-Wire
Wire Size	#18 AWG to #8 AWG

Logistics

Carton Quantity	5
-----------------	---

Product Assets

[Catalog Page - Bryant H-25 Catalog page](#)
[Catalogs - Bryant Full Line Catalog](#)

Related Products

[21415 - Locking Devices, Bryant Power Interrupting, Industrial, Male Plug, 30A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal and White](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRY-21420-SPEC-EN | REV 5/2023