BRYANT®

Industrial Grade, Toggle Switches, Motor Disconnects, Double Pole, 30A 600V AC, Side Wired Only, With NEMA 3R Enclosure

By Bryant
Catalog # 30302D

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Double Pole, 30A 600V AC, Side Wired Only, Black, With NEMA 3R Enclosure

Application

Red Slide

General

Catalog Number	30302D
EU RoHS Indicator	No
Enclosure Type	NEMA 3R
Environmental Conditions	Indoor and Outdoor
Item Type	Enclosed Switch
Load Capacity	Inductive
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2 Pole
OEM Brand Name	Hubbell Bryant
Operating Cycles	10,000 Cycles Minimum
Operating Temperature	Minimum Continuous -40 Deg C without Impact
Series	Non-Fused
Style	Standard Duty
Type	Disconnect Switches
UPC	781786631571

Dimensions

Display Size	Standard Sized Product

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Phase	Single Phase
Voltage Rating	600V AC kV
Voltage Rating Description	600V AC kV
Wattage	18000

Certifications And Compliance

Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	4

Product Assets

Catalog Page - BRY E-12 Catalog Page
Catalog Page - BRY G-3 Catalog Page
Catalog Page - BRY G-6 Catalog Page
Catalogs - Bryant Full Line Catalog
Literature - General Literature - Motor Controllers and Disconnects
Literature - General Literature - BRYANT® Wiring Devices
Specifications - 30302D

©2024 Hubbell Incorporated. All rights reserved