BRYANT®

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 32A 220-240V, Watertight

By Bryant Catalog # 332B6W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 32A 220-240V, 2-Pole 3-Wire Grounding, Terminal Screw, Blue, Watertight

Features

- Industrial Grade
- Male Flanged Inlet
- 32A 220-240V
- 2-Pole 3-Wire Grounding
- Terminal Screw

OEM Brand Name

Application

High Ampacity Watertight Connections

General

Catalog Number 332B6W Color Blue **EU RoHS Indicator** Yes **Environmental Conditions** Watertight Insulation Insulated Body Item Type Single Flanged Composite Material Material - Mounting Hardware **Screw Mounting** Number Of Poles 2-Pole

Series Watertight - IP67
Temperature Rating Maximum Continuous: 7

emperature Rating Maximum Continuous: 75° C;
Minimum Continuous: -40° C

Hubbell Bryant



w/o impact
Type Inlet

UPC 781786250505

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 32 A Connectivity Pressure Terminal Screws Current / Amperage Rating 32 A **Current Rating** 32 A Withstands 3000V Minimum in Dielectric Strength 200-250 V Voltage Rating Voltage Rating Description 200-250V Wattage 8000

Conductor Related

Number Of Wires 3-Wire

Product Assets

Specifications - 332B6W

