BRYANT[®]

Locking Devices, Locking Devices, Industrial, Female Connector Body, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal and White



By Bryant Catalog # 3764

Locking Devices, Industrial, Female Connector Body, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black and White

> 3764 Black

No

General

Application Catalog Number Color EU RoHS Indicator Environmental Conditions

Insulation Item Type

Material Material - Mounting Hardware Number Of Poles OEM Brand Name Style Temperature Rating

Type UPC

Dimensions

Dimensions Display Size Height Length Width 6.50 in x 2.56 in x 2.56 in Standard Sized Product 2.56 in 6.5 in 2.56 in

Heavy Duty Industrial

Additional Means

For Replacement Use

Insulated Body

Composite Cord Mounted

Hubbell Bryant Extra Heavy Duty

Connector Body

781786652552

3-Pole

Indoor Dry Unless Protected By

50A Heavy Duty Connector-

Maximum Continuous: 75° C;

Minimum Continuous: -40° C w/o impact, -25° with impact.

Electrical Ratings

Amperage Rating	50 A
Connectivity	Pressure Terminal Screws
Current Rating	50 A
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

Conductor Related

Conductor Range Number Of Wires Number of Conductors Wire Size	#6 AWG 4-Wire 4-Wire Grounding #18 AWG to #8 AWG
Logistics Carton Quantity	10

Product Assets

Catalog Page - BRY H-22 Catalog Page Catalogs - Bryant Full Line Catalog



©2024 Hubbell Incorporated. All rights reserved BRY-3764-SPEC-EN | REV 6/2024