BRYANT®

Locking Devices, Locking Devices, Industrial, Flush Receptacle, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non- NEMA, Screw Terminal, Black

By Bryant Catalog # 3769

Locking Devices, Industrial, Flush Receptacle, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non- NEMA, Screw Terminal, Black



Extra Heavy Duty Industrial Specification Grade

General

Color Black

Environmental Conditions Indoor Dry Unless Protected

By Additional Means

Item TypeSingle ReceptacleMaterialComposite

Material - Mounting Hardware Screw Mounting

Number Of Poles 3-Pole

OEM Brand Name Hubbell Bryant
Style Extra Heavy Duty
Type Receptacle
UPC 781786652804

Dimensions

Dimensions 3.28 in x 2.12 in x 2.44 in
Display Size Standard Sized Product

Height 2.44 in Length 3.28 in Width 2.12 in

Electrical Ratings

Amperage Rating 50 A

Connectivity Pressure Terminal Screws

Current Rating 50 A

Phase Multi Phase

Voltage Rating 250 VDC/600 VAC Voltage Rating Description 250 VDC/600 VAC



Conductor Related

Number Of Wires 4-Wire

Wire Size #14 AWG to #10 AWG

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant H-22 Catalog page Catalog Page - Bryant Q-18 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

3765 - Locking Devices, Locking Devices, Industrial, Male Plug, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black and White

7382 - Wallplates and Boxes, Non-Weatherproof Covers, 1-Gang, 1) 50A Locking Opening, Standard Size, Cast Aluminum, Less Flip Lid

7383 - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1) 50A Locking Opening, Standard Size, Cast Aluminum

7774CR - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1) 50A Locking Opening, Standard Size, Yellow Polycarbonate SS750 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1) 50A Twist-Lock® Opening, Standard Size, Stainless Steel

