



# Locking Devices, Locking Devices, Industrial, Flush Receptacle, 50A 250V DC/600V AC, 2-Pole 3-Wire Grounding, Non- NEMA, Screw Terminal, Black

By Bryant  
Catalog # 3771



Locking Devices, Industrial, Flush Receptacle, 50A 250V DC/600V AC, 2-Pole 3-Wire Grounding, Non- NEMA, Screw Terminal, Black

## Application

Extra Heavy Duty Industrial Specification Grade

## General

Color	Black
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Single Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Bryant
Style	Extra Heavy Duty
Type	Receptacle
UPC	781786652903

## Dimensions

Dimensions	3.28 in x 2.12 in x 2.44 in
Display Size	Standard Sized Product
Height	2.44 in
Length	3.28 in
Width	2.12 in

## Electrical Ratings

Amperage Rating	50 A
Connectivity	Pressure Terminal Screws
Current Rating	50 A
Phase	Single Phase
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

## Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

## Logistics

Carton Quantity	10
-----------------	----

## Product Assets

[Catalog Page - Bryant H-22 Catalog page](#)  
[Catalog Page - Bryant Q-18 Catalog page](#)  
[Catalogs - Bryant Full Line Catalog](#)

## Related Products

[7774CR - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1\) 50A Locking Opening, Standard Size, Yellow Polycarbonate](#)  
[3763 - Locking Devices, Locking Devices, Industrial, Male Plug, 50A 250V DC 600V AC, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Black and White](#)  
[SS750 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1\) 50A Twist-Lock® Opening, Standard Size, Stainless Steel](#)  
[7382 - Wallplates and Boxes, Non-Weatherproof Covers, 1- Gang, 1\) 50A Locking Opening, Standard Size, Cast Aluminum, Less Flip Lid](#)  
[7383 - Wallplates and Boxes, Weatherproof Covers, 1- Gang, 1\) 50A Locking Opening, Standard Size, Cast Aluminum](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
BRY-3771-SPEC-EN | REV 5/2023