



Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 125A 380/415V, Screw Terminals, Watertight

By Bryant
Catalog # 4125B6W



Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 125A 380/415V, 3-Pole 4-Wire Grounding, Screw Terminals, Red, Watertight

Features

- Industrial Grade
- Male Flanged Inlet
- 125A 380/415V
- 3-Pole 4-Wire Grounding
- Screw Terminals

Application

High Ampacity Watertight Connections

General

| | |
|------------------------------|--|
| Catalog Number | 4125B6W |
| Color | Red |
| EU RoHS Indicator | Yes |
| Environmental Conditions | Watertight |
| Insulation | Insulated Body |
| Item Type | Single Flanged |
| Material | Composite |
| Material - Mounting Hardware | Screw Mounting |
| Number Of Poles | 3-Pole |
| OEM Brand Name | Hubbell Bryant |
| Series | Watertight - IP67 |
| Temperature Rating | Maximum Continuous: 75° C; Minimum Continuous: -40° C |

| | |
|------|-----------------------|
| Type | w/o impact |
| UPC | Inlet 781786250895 |

Dimensions

| | |
|--------------|------------------------|
| Display Size | Standard Sized Product |
|--------------|------------------------|

Electrical Ratings

| | |
|----------------------------|-----------------------------|
| Amperage Rating | 125 A |
| Connectivity | Pressure Terminal Screws |
| Current / Amperage Rating | 125 A |
| Current Rating | 125 A |
| Dielectric Strength | Withstands 3000V Minimum in |
| Voltage Rating | 380-415 V |
| Voltage Rating Description | 380-415V |
| Wattage | 51875 |

Conductor Related

| | |
|-----------------|--------|
| Number Of Wires | 4-Wire |
|-----------------|--------|

Product Assets

[Specifications - 4125B6W](#)