BRYANT®

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 63A 125/250V, Screw Terminals, Watertight

By Bryant Catalog # 463B6W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 63A 125/250V, 3-Pole 4-Wire Grounding, Screw Terminals, Red, Watertight

Features

- Industrial Grade
- Male Flanged Inlet
- 63A 125/250V
- 3-Pole 4-Wire Grounding
- Screw Terminals

Application

High Ampacity Watertight Connections

General

Catalog Number 463B6W Red Color **EU RoHS Indicator** Yes **Environmental Conditions** Watertight Insulation Insulated Body Item Type Single Flanged Material Composite Material - Mounting Hardware **Screw Mounting** Number Of Poles 3-Pole

OEM Brand Name Hubbell Bryant Series Watertight - IP67

Temperature Rating Maximum Continuous: 75° C; Minimum Continuous: -40° C



 w/o impact

 Type
 Inlet

 UPC
 781786251526

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 63 A Connectivity Pressure Terminal Screws Current / Amperage Rating 63 A **Current Rating** 63 A Withstands 3000V Minimum in Dielectric Strength 380-415 V Voltage Rating Voltage Rating Description 380-415V Wattage 26145

Conductor Related

Number Of Wires 4-Wire

Product Assets

Specifications - 463B6W

