BRYANT®

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 125A 380/415V, Screw Terminals, Watertight

By Bryant Catalog # 5125B6W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 125A 380/415V, 4-Pole 5-Wire Grounding, Screw Terminals, Red, Watertight

Features

- Industrial Grade
- Male Flanged Inlet
- 125A 380/415V
- 4-Pole 5-Wire Grounding
- Screw Terminals

Application

High Ampacity Watertight Connections

General

Catalog Number 5125B6W Color Red **EU RoHS Indicator** Yes **Environmental Conditions** Watertight Insulation Insulated Body Item Type Single Flanged Material Composite Material - Mounting Hardware **Screw Mounting**

Number Of Poles 4-Pole

OEM Brand Name Hubbell Bryant

Series Watertight - IP67

Temperature Rating Maximum Continuous: 75° C; Minimum Continuous: -40° C

Type Inlet

UPC 781786251656

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 125 A
Connectivity Pressure Terminal Screws
Current / Amperage Rating 125 A
Current Rating 125 A
Dielectric Strength Withstands 3000V Minimum in
Voltage Rating 200/346 V 240/415 V
Voltage Rating Description 200/346V 240/415V

51875

Conductor Related

Number Of Wires 5-Wire

Product Assets

Wattage

Specifications - 5125B6W

