# BRYANT®

## Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female Connector Body, 16A 380/415V, Screw Terminals, Splash Proof



By Bryant Catalog # 516C6S

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female Connector Body, 16A 380/415V, 4-Pole 5-Wire Grounding, Screw Terminals, Red, Splash Proof

### Features

- Industrial Grade
- Female Connector Body
- 16A 380/415V
- 4-Pole 5-Wire Grounding
- Screw Terminals

### Application

High Ampacity Connections

### General

Catalog Number Color EU RoHS Indicator Environmental Conditions Insulation Item Type Material Material - Mounting Hardware Number Of Poles OEM Brand Name Series Temperature Rating 516C6S Red Yes Watertight Insulated Body Splashproof Composite Cord Mounted 4-Pole Hubbell Bryant Splashproof - IP44 Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact, -25° with impact. Type UPC Connector 781786252295

### Dimensions

Display Size

Standard Sized Product

### Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Voltage Rating Voltage Rating Description 16 A Pressure Terminal Screws 16 A 16 A 200/346 V 240/415 V 200/346V 240/415V

### **Conductor Related**

Conductor Range Number Of Wires Number of Conductors #14 AWG to #10 AWG 5-Wire 5-Wire Grounding

### **Certifications And Compliance**

Nema Rating

Non-NEMA

### **Product Assets**

Specifications - 516C6S



©2024 Hubbell Incorporated. All rights reserved BRY-516C6S-SPEC-EN | REV 10/2024