BRYANT®

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 20A 3-Phase Wye 120/208V AC, Watertight

By Bryant Catalog # 520B9W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male Flanged Inlet, 20A 3-Phase Wye 120/208V AC, 4-Pole 5-Wire Grounding, Screw Terminals, Blue, Watertight

Features

- Industrial Grade
- Male Flanged Inlet
- 20A 3-Phase Wye 120/208V AC
- 4- Pole 5-Wire Grounding
- Screw Terminals

Application

High Ampacity Watertight Connections

General

Catalog Number520B9WColorBlueEU RoHS IndicatorYesEnvironmental ConditionsWatertigInsulationInsulatedItem TypeSingle FlatMaterialComposiMaterial - Mounting HardwareScrew MeNumber Of Poles4-PoleOEM Brand NameHubbell ESeriesWatertigTemperature RatingMaximum

Blue Yes Watertight Insulated Body Single Flanged Composite Screw Mounting 4-Pole Hubbell Bryant Watertight - IP67 Maximum Continuous: 75° C; Minimum Continuous: -40° C



Type UPC w/o impact Inlet 781786251748

20 A

5-Wire

Dimensions

Display Size

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Dielectric Strength Voltage Rating Voltage Rating Description Wattage

Pressure Terminal Screws 20 A 20 A Withstands 3000V Minimum in 3 Phase Y 120/208 V 3 Phase Y 120/208V 4160

Standard Sized Product

Conductor Related

Number Of Wires

Product Assets

Specifications - 520B9W

