BRYANT[®]

Locking Devices, Industrial, Flush Receptacle, 20A 3-Phase Wye 120/208V AC, 4-Pole 5-Wire Grounding, L21-20R, Screw Terminal, Black

By Bryant Catalog # 72120FR

Locking Devices, Industrial, Flush Nylon Receptacle, 20A 3-Phase Wye 120/208V AC, 4-Pole 5-Wire Grounding, L21-20R, Screw Terminal, Black

72120FR

Additional Means

Screw Mounting

Hubbell Bryant

Receptacle Receptacle

781786701236

Single Receptacle

Composite

4-Pole

Yes

Extra Heavy Duty Industrial Specification Grade

Indoor Dry Unless Protected By

20A Single Nylon Receptacle

General

Application

Catalog Number Color EU RoHS Indicator Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles OEM Brand Name Style Type

UPC

Dimensions

Dimensions	3.28 in x 1.70 in x 1.24 in
Display Size	Standard Sized Product
Height	1.24 in
Length	3.28 in
Width	1.7 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current Rating	20 A
Phase	Three Phase
Voltage Rating	3 Phase Y 120/208 VAC
Voltage Rating Description	3 Phase Y 120/208V AC

Conductor Related

Number Of Wires Wire Size 5-Wire #14 AWG to #8 AWG



Certifications And Compliance

Nema Rating	L21-20R
Standards - RoHS Compliance	СМ
Status	

Logistics

Carton Quantity	10
Pallet Quantity	2340

Product Assets

Catalog Page - BRY H-10 Catalog Page Catalog Page - BRY Q-18 Catalog Page Catalogs - Bryant Full Line Catalog



©2024 Hubbell Incorporated. All rights reserved BRY-72120FR-SPEC-EN | REV 6/2024