BRYANT®

Locking Devices, Bryant Midget Locking, Industrial, Flanged Inlet, 15A 125V, 2-Pole 3-Wire Grounding, ML-2P, Screw Terminal, Black & White

By Bryant Catalog # 7595MB





Application

Extra Heavy Duty Industrial

General

Color White

Indoor Dry Unless Protected **Environmental Conditions**

By Additional Means

Insulation Insulated Body

Item Type 15A Midget Flanged Inlet

Material Composite Material - Mounting Hardware Screw Mounting

Number Of Poles 2-Pole

OEM Brand Name Hubbell Bryant Grounding Style

Temperature Rating Maximum Continuous: 75° C:

Minimum Continuous: -40° C

w/o impact

Type Flanged Inlet UPC 781786671409

Dimensions

Dimensions 2.06 in x 1.62 in x 1.17 in

Display Size Midget Locking

Height 1.17 in Length 2.06 in Width 1.62 in

Electrical Ratings

Amperage Rating 15 A

Screw Terminals Connectivity

Current Rating

Withstands 3000V Minimum Dielectric Strength

Voltage Rating 125 V 125V Voltage Rating Description

Conductor Related

Number Of Wires 3-Wire

Wire Size #18 AWG to #12 AWG

Certifications and Compliance

Nema Rating ML-2P

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant H-4 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

7593NC - Locking Devices, Bryant Midget Locking, Industrial, Female Connector Body, 15A 125V, 2-Pole 3-Wire Grounding,

ML-2R, Screw Terminal, Black & White

7400BCR - Straight Blade Devices, Locking Devices, Accessories, Weatherproof Boot for Midget Devices, For 15A,

2-Pole 2-Wire, Yellow

7596ER - Locking Devices, Bryant Midget Locking, Industrial, Flanged Receptacle, 15A 125V, 2-Pole 3-Wire Grounding, ML-

2R, Screw Terminal, Black & White

7594NP - Locking Devices, Bryant Midget Locking, Industrial, Male Plug, 15A 125V, 2-Pole 3-Wire Grounding, ML-2P, Screw

Terminal, Black

