BRYANT®

Watertight Series, Locking Receptacle, 20A 3- Phase 480V AC, 3-Pole 4-Wire Grounding, NEMA L16-20R, Yellow

By Bryant Catalog # BRY67W76

Watertight Series, Locking Receptacle, 20A 3-Phase 480V AC, 3-Pole 4-Wire Grounding, NEMA L16-20R, Yellow

Features

- Impact-resistant PBT material lid and cover plate
- Stainless steel mounting hardware
- Lockable cover meets OSHA Lockout/Tagout regulations
- Thermoplasticelastomer seal

General

Color Item Type Number Of Poles Performance Yellow 20A Watertight Single Receptacle 3-Pole

- Moisture resistance: UL Listed to 3R, 3RX, 4, 4X, wet and damp locations (portable outlet boxes)
- UV resistance:All exposed materials are UV stabilized
- Flammability:UL94V0 (boxes, covers, and plates)

Receptacle 781786379282

Dimensions

Type

UPC

 Dimensions
 4.56 in x 3.10 in x 3.45 in

 Height
 3.45 in

 Length
 4.56 in

 Width
 3.10 in

Electrical Ratings

Amperage Rating	20 A
Voltage Rating	3 Phase 480 VAC
Voltage Rating Description	3 Phase 480 VAC

Conductor Related

Number Of Wires4-WireWire Size#18 AWG to #8 AWG



Certifications and Compliance

Industry Standard(s)

- IP69K in use
- Listed to UL498
- Certified to CSA C22.2 No. 42
- Meets NEMA® WD-1, WD-6, and ANSI Standards
- IP66 Suitability

L16-20R

5

• NSF Certified (plugs, connectors and receptacles)

Nema Rating

Logistics

Carton Quantity

Product Assets

Catalog Page - Bryant I-6 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

BRY60CM83WAK - Watertight Series, Adapter Kit, 3/4" NPT, White BRY60CM84WA - Watertight Series, FD Box, 1" NPT, White BRY6055 - Watertight Angled Adapter, Gray BRY6084AK - Watertight Series, Adapter Kit, 1" NPT, Gray BRY60CM84WAK - Watertight Series, Adapter Kit, 1" NPT, White

