BRYANT®

Locking Devices, Industrial, Female Connector Body, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black and White

By Bryant Catalog # CS6364

Locking Devices, Industrial, Female Connector Body, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Heavy Duty Black



- Box terminal with hex socket threaded slug, permits high clamping pressure on conductors without damaging strands
- Thermoplastic polyester interior provides heat resistance and impact strength
- Oversized contacts minimize operating temperature

Application

Heavy Duty Industrial

General

Color Black

Environmental Conditions Indoor Dry Unless Protected

By Additional Means

InsulationInsulated BodyItem TypeConnectorMaterialCompositeMaterial - Mounting HardwareCord Mounted

Number Of Poles 3-Pole

OEM Brand Name Hubbell Bryant
Style Extra Heavy Duty

Temperature Rating Maximum Continuous: 75° C; Minimum Continuous: -40° C

w/o impact, -25° with impact. Nylon

Type Connector Body UPC 781786611771

Dimensions

Dimensions 6.50 in x 2.56 in x 2.56 in Display Size Standard Sized Product

Height 2.56 in Length 6.50 in Width 2.56 in



Electrical Ratings

Amperage Rating 50 A

Connectivity Pressure Terminal Screws

Current Rating 50 A

Voltage Rating 125/250 VAC Voltage Rating Description 125/250 VAC

Conductor Related

Conductor Range #6 AWG

Number Of Conductors 4-Wire Grounding

Number Of Wires 4-Wire

Wire Size #8 AWG to #4 AWG

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant H-21 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

7717B - Locking Devices, Accessories, Weatherproof Boot,

Nylon Connector Body, For 50A Black

7716B - Locking Devices, Accessories, Weatherproof Boot,

Nylon Plug, For 50A Black

CS6365 - Locking Devices, Industrial, Male Plug, 50A

125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw

Terminal, Black and White

CS6375A - Locking Devices, Industrial, Flanged Inlet, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw

Terminal, Steel

