



Locking Devices, Industrial, Flanged Inlet, 50A Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Steel

By Bryant
Catalog # CS8175A



Locking Devices, Industrial, Flanged Inlet, 50A Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Steel

Application

Extra Heavy Duty Industrial

General

Catalog Number	CS8175A
Color	Metallic
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Insulation	Insulated Body
Item Type	50A Male Flanged Inlet
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Bryant
Style	Extra Heavy Duty
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact
Type	Flanged Inlet
UPC	781786253148

Dimensions

Dimensions 2.77 in x 3.50 in x 3.50 in

Display Size	Standard Sized Product
Height	3.5 in
Length	2.77 in
Width	3.5 in

Electrical Ratings

Amperage Rating	50 A
Connectivity	Pressure Terminal Screws
Current Rating	50 A
Dielectric Strength	Withstands 3000V Minimum in
Voltage Rating	3 Phase 480 VAC
Voltage Rating Description	3 Phase 480V AC

Conductor Related

Number Of Wires	4-Wire
Wire Size	#18 AWG to #8 AWG

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - BRY H-21 Catalog Page](#)
[Catalogs - Bryant Full Line Catalog](#)
[Specifications - CS8175A](#)