BRYANT®

Locking Devices, Locking Devices, Industrial, Flanged Inlet, 50A 250V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Steel

By Bryant Catalog # CS8275A

Locking Devices, Industrial, Flanged Inlet, 50A 250V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Heavy Duty Black



Extra Heavy Duty Industrial

General

Insulation

Catalog Number CS8275A
Color Metallic
EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means Insulated Body

Item Type 50A Male Flanged Inlet

Material Composite

Material - Mounting Hardware Screw Mounting

Number Of Poles 2-Pole

OEM Brand Name Hubbell Bryant
Style Extra Heavy Duty

Temperature Rating Maximum Continuous: 75° C;

Minimum Continuous: -40° C

w/o impact

Type Flanged Inlet UPC 781786253162

Dimensions

Dimensions 2.77 in x 3.50 in x 3.50 in



Display Size Standard Sized Product

Height 3.5 in
Length 2.77 in
Width 3.5 in

Electrical Ratings

Amperage Rating 50 A

Connectivity Pressure Terminal Screws

Current Rating 50 A

Dielectric Strength Withstands 3000V Minimum in

Voltage Rating 250 VAC Voltage Rating Description 250 VAC

Conductor Related

Number Of Wires 3-Wire

Wire Size #18 AWG to #8 AWG

Logistics

Carton Quantity 10

Product Assets

Catalog Page - BRY H-21 Catalog Page Catalogs - Bryant Full Line Catalog

Specifications - CS8275A

