BRYANT®

Locking Devices, Locking Devices, Industrial, Flanged Inlet, 50A 480V AC, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Black

By Bryant Catalog # CS8475A

Locking Devices, Industrial, Flanged Inlet, 50A 480V AC, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Heavy Duty Black

Application

Extra Heavy Duty Industrial

General

Catalog Number Color EU RoHS Indicator Environmental Conditions

Insulation Item Type Material Material - Mounting Hardware Number Of Poles OEM Brand Name Style Temperature Rating

Type UPC

Dimensions

Dimensions

CS8475A Metallic No Indoor Dry Unless Protected By Additional Means Insulated Body 50A Male Flanged Inlet Composite Screw Mounting 2-Pole Hubbell Bryant Extra Heavy Duty Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact Flanged Inlet 781786253322

2.77 in x 3.50 in x 3.50 in



Display Size Height Length Width Standard Sized Product 3.5 in 2.77 in 3.5 in

Electrical Ratings

Amperage Rating
Connectivity
Current Rating
Dielectric Strength
Voltage Rating
Voltage Rating Description

50 A Pressure Terminal Screws 50 A Withstands 3000V Minimum in 480 VAC 480V AC

3-Wire

10

#18 AWG to #8 AWG

Conductor Related

Number Of Wires Wire Size

Logistics

Carton Quantity

Product Assets

Catalog Page - BRY H-21 Catalog Page Catalogs - Bryant Full Line Catalog Specifications - CS8475A

