BRYANT®

Replaced By GFRWR15LA - Heavy Duty Commercial Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 15A, Light Almond

By Bryant Catalog # GFWRST15LA

Power Protection Devices, Receptacle, Self Test, GFCI, WR, Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Light Almond

Features

- Patented AUTOGUARD® self test technology
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Protects against line and load reversal, no power to the face or downstream if device is miswired

General

Style

Туре

Catalog Number Color EU RoHS Indicator Series Specifications GFWRST15LA Light Almond Contact Manufacturer Heavy Duty • Base - Nylon

- Dase Nyior
- Face Nylon
- Ground Contacts Brass
- Mounting Screws Zinc plated steel
- Mounting Strap Zinc plated
 steel
- Power Contacts Brass

Standard

Weather Resistant



UPC	883778122453
Electrical Ratings	
Amperage Rating Current / Amperage Rating Voltage Rating Description	15 A 15 A 125 V
Certifications And Complia	ance
Industry Standard(s)	Meets All NEC® Re

Industry Standard(s)	Meets All NEC® Requirements
Nema Rating	5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK K-8 Catalog Page Catalogs - WDK Catalog Full 2024 Literature - 2015 UL GFCI Requirements Literature - AUTOGUARD® Self Test Ground Fault Receptacles Sales Drawings - WDK_GFWRST15_DRAWING_PDF Specifications - GFWRST15LA

