BRYANT®

Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Black

By Bryant Catalog # HBL15FRSBK

Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Black

Features

- Threaded Stud Termination
- 150 Amp Series
- Black

Application

Extra Heavy Duty Industrial

Performance

- Electrical Amperage Rating 150A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #8 to #2 AWG

General

Catalog Number	HBL15FRSBK
Color	Black
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By
	Additional Means
Item Type	Female Receptacle
Material	Brass/Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	1-Pole
Series	Series 15
Specifications	 Base Compound -
	Thermoplastic Elastomer
	(TPE)
	 Contact Material - Brass
	 Mounting Hole - 3x Ø .20"
	 Retaining Screw Material -
	Nylon
	Termination - 5/16-18

 Termination - 5/16-18 Threaded Stud Female

Receptacle, Stud Type

Standard Sized Product

#4 AWG Type SC/PPC Wire

783585458274

Threaded Stud

Single Phase

600V AC/DC

150 A

150 A

150 A

90000

None

Туре UPC

Dimensions

Display Size

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating **Current Rating** Phase Voltage Rating Description Wattage

Conductor Related

Number Of Wires Wire Size

Certifications And Compliance

Industry Standard(s)	 National Electric Code (NEC), ANSI/NFPA 70 UL and cUL Listed UL Enclosure Types 3R, 4X, 12
Nema Rating	Non-NEMA
Logistics	
Carton Quantity	25
Product Assets	

Catalog Page - WDK H-3 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices Specifications - HBL15FRSBK



Style