## **BRYANT®**

# Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Blue

By Bryant Catalog # HBL15FRSBL

Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Blue



· Threaded Stud Termination

• 150 Amp Series

Blue

### **Application**

Extra Heavy Duty Industrial

### Performance

• Electrical - Amperage Rating - 150A Maximum

• Electrical - Voltage Ratings - 600V AC Maximum

• 250V DC Maximum

 Mechanical - Product Identification - Ratings are a permanent part of device

• Mechanical - Terminal Accommodation - #8 to #2 AWG

#### General

Catalog Number HBL15FRSBL

Color Blue EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Item Type Female Receptacle

Material Brass/Thermoplastic

Material - Mounting Hardware Screw Mounting

Number Of Poles 1-Pole Series Series 15

Specifications

• Base Compound -

Thermoplastic Elastomer (TPE)

• Contact Material - Brass

• Mounting Hole - 3x Ø .20"

 Retaining Screw Material -Nylon

• Termination - 5/16-18 Threaded Stud

Style Female



Type Receptacle, Stud Type UPC 783585458304

**Dimensions** 

Display Size Standard Sized Product

**Electrical Ratings** 

Amperage Rating 150 A

Connectivity Threaded Stud

Current / Amperage Rating 150 A
Current Rating 150 A

Phase Single Phase Voltage Rating Description 600V AC/DC Wattage 90000

**Conductor Related** 

Number Of Wires None

Wire Size #4 AWG Type SC/PPC Wire

**Certifications And Compliance** 

Industry Standard(s)

• National Electric Code

(NEC), ANSI/NFPA 70

UL and cUL Listed

UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25

**Product Assets** 

Catalog Page - WDK H-3 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices

Specifications - HBL15FRSBL

