

## Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Green

By Bryant  
Catalog # HBL15FRSGN



Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, Green

### Features

- Threaded Stud Termination
- 150 Amp Series
- Green

### Application

Extra Heavy Duty Industrial

### Performance

- Electrical - Amperage Rating - 150A Maximum
- Electrical - Voltage Ratings - 600V AC Maximum
- 250V DC Maximum
- Mechanical - Product Identification - Ratings are a permanent part of device
- Mechanical - Terminal Accommodation - #8 to #2 AWG

### General

Catalog Number	HBL15FRSGN
Color	Green
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Female Receptacle
Material	Brass/Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	1-Pole
Series	Series 15
Specifications	<ul style="list-style-type: none"> <li>• Base Compound - Thermoplastic Elastomer (TPE)</li> <li>• Contact Material - Brass</li> <li>• Mounting Hole - 3x Ø .20"</li> <li>• Retaining Screw Material - Nylon</li> <li>• Termination - 5/16-18 Threaded Stud</li> </ul>
Style	Female

Type Receptacle, Stud Type  
UPC 783585458311

### Dimensions

Display Size Standard Sized Product

### Electrical Ratings

Amperage Rating 150 A  
Connectivity Threaded Stud  
Current / Amperage Rating 150 A  
Current Rating 150 A  
Phase Single Phase  
Voltage Rating Description 600V AC/DC  
Wattage 90000

### Conductor Related

Number Of Wires None  
Wire Size #4 AWG Type SC/PPC Wire

### Certifications And Compliance

Industry Standard(s)

- National Electric Code (NEC), ANSI/NFPA 70
- UL and cUL Listed
- UL Enclosure Types 3R, 4X, 12

Nema Rating Non-NEMA

### Logistics

Carton Quantity 25

### Product Assets

[Catalog Page - WDK H-3 Catalog Page](#)  
[Catalogs - WDK Catalog Full 2024](#)  
[Catalogs - Bryant Full Line Catalog](#)  
[Literature - Single Pole Devices](#)  
[Specifications - HBL15FRSGN](#)