# **BRYANT®**

# Single Pole Products, Male Inlet, **Threaded Stud Termination, 150 Amp Series, Red**

By Bryant Catalog # HBL15MRSR

Single Pole Products, Male Inlet, Threaded Stud Termination, 150 Amp Series, Red

# **Features**

- Threaded Stud Termination
- 150 Amp Series
- Red

#### **Application**

Extra Heavy Duty Industrial

#### Performance

- Electrical Amperage Rating 150A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #8 to #2 AWG

#### General

Catalog Number HBL15MRSR Color Red

**EU RoHS Indicator** 

**Environmental Conditions** 

Item Type

Material

Material - Mounting Hardware

Number Of Poles

Series

Specifications

No

Indoor Dry Unless Protected By

Additional Means

Male Inlet

Brass/Thermoplastic Screw Mounting

1-Pole

Series 15

• Base Compound -Thermoplastic Elastomer

(TPE)

- Contact Material Brass
- Mounting Hole 3x Ø .20"
- Retaining Screw Material -Nylon
- Termination 5/16-18 Threaded Stud

Style Male



Туре Receptacle, Stud Type **UPC** 783585458243

### **Dimensions**

Display Size Standard Sized Product

# **Electrical Ratings**

Amperage Rating 150 A

Threaded Stud Connectivity

Current / Amperage Rating 150 A

Current Rating 150 A Phase Single Phase

Voltage Rating Description 600V AC/DC 90000

Wattage

#### **Conductor Related**

Number Of Wires None

Wire Size #4 AWG Type SC/PPC Wire

# **Certifications And Compliance**

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

Non-NEMA Nema Rating

# Logistics

Carton Quantity 25

#### **Product Assets**

Catalog Page - WDK H-3 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices Specifications - HBL15MRSR

