# **BRYANT®**

# Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Blue

By Bryant Catalog # HBLFRBBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Blue



# **Application**

**High Ampacity Connections** 

#### General

Color

**Environmental Conditions** 

Item Type Material

Material - Mounting Hardware Number Of Poles

Performance

Blue

• Bleu

Indoor Dry Unless Protected By Additional Means

Flanged Single Thermoplastic

Screw Mounting

1-Pole

• Electrical - Amperage Rating - 400A Maximum

Electrical - Voltage Ratings- 600V AC Maximum

• 250V DC Maximum

 Environmental -Flammability - HB per UL94 or CSA 22.2. 0.17

 Mechanical - Product Identification - Ratings are a permanent part of device

 Mechanical - Terminal Accommodation - #4 to

4/0 AWG

Series 16

Style Bus Bar Mount Female

 Type
 Receptacle

 UPC
 783585192673

#### **Dimensions**

Display Size Standard Sized Product

#### **Electrical Ratings**

Amperage Rating 400 A

Connectivity Screw Terminals

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase

Voltage Rating Description 600V AC/DC

Wattage 240000

#### **Conductor Related**

Wire Size #4 AWG to #4/0 AWG

### **Certifications and Compliance**

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25

## **Product Assets**

Catalog Page - Bryant L-6 Catalog page Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices



Series