BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Brown

By Bryant Catalog # HBLFRBBN

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Brown



Application

High Ampacity Connections

General

Color

Environmental Conditions

Item Type Material

Material - Mounting Hardware Number Of Poles

Performance

Brown

Marron

Indoor Dry Unless Protected By Additional Means

Flanged Single Thermoplastic

Screw Mounting

1-Pole

• Electrical - Amperage Rating - 400A Maximum

Electrical - Voltage Ratings - 600V AC Maximum

• 250V DC Maximum

Environmental -Flammability - HB per UL94 or CSA 22.2. 0.17

• Mechanical - Product Identification - Ratings are a permanent part of device

Mechanical - Terminal Accommodation - #4 to

4/0 AWG

Series Series 16

Style Bus Bar Mount Female

Туре Receptacle UPC 783585192680

Dimensions

Display Size Standard Sized Product

Electrical Ratings

400 A Amperage Rating

Connectivity Screw Terminals

Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase

600V AC/DC Voltage Rating Description Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications and Compliance

Industry Standard(s)

· National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25

Product Assets

Catalog Page - Bryant L-6 Catalog page Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices

