BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, White

By Bryant Catalog # HBLFRBW

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, White

Features

- Industrial Grade
- · Female Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number
Color
EU RoHS Indicator
Environmental Conditions

Item Type Material -

Material - Mounting Hardware Number Of Poles

Series

Specifications

HBLFRBW White No

Indoor Dry Unless Protected By

Additional Means Flanged Single Thermoplastic Screw Mounting

1-Pole Series 16

 Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x #10-32
- Retaining Screw Material -Nylon
- Termination 5/16-18 UNC-2B Threaded Hole



Style Bus Bar Mount Female

Type Receptacle UPC 783585192642

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A

Connectivity Screw Terminals

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase

Voltage Rating Description 600V AC/DC Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25

Product Assets

Catalog Page - WDK H-7 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices Specifications - HBLFRBW

