BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Orange



By Bryant Catalog # HBLFRO

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Orange

Application

High Ampacity Connections

General

Color Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Performance

Orange Indoor Dry Unless Protected By Additional Means Panel Mount Receptacle Elastomer / Elastomeric Threaded Thru-Hole 1-Pole

- Electrical Amperage Rating - 400A Maximum
- Electrical Voltage Ratings - 600V AC Maximum
- 250V DC Maximum
- Environmental -Flammability - HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification - Ratings are a permanent part of device
- Mechanical Terminal Accommodation - #4 to 4/0 AWG

Series 16 Female Double Set Screw Receptacle 783585112633

Dimensions

Series

Style

Type

UPC

Display Size

Standard Sized Product

Electrical Ratings

Amperage Rating	400 A
Connectivity	Double Set Screw
Current / Amperage Rating	400 A
Current Rating	400 A
Phase	Single Phase
Voltage Rating Description	600V AC/DC
Wattage	240000
Conductor Related	

Number Of Wires1-WireWire Size#4 AWG to #4/0 AWG

Certifications and Compliance

Industry Standard(s)

Nema Rating

Logistics

Carton Quantity

Product Assets

Catalog Page - Bryant L-5 Catalog page Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices



National Electric Code

• UL and cUL Listed

12

25

Non-NEMA

(NEC), ANSI/NFPA 70

• UL Enclosure Types 3R, 4X,