# **BRYANT®**

# Heavy Duty Products, Single Pole Devices, Industrial Grade, Female, Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Blue

By Bryant Catalog # HBLFRSBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female, Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Blue

## **Features**

- Industrial Grade
- Female
- Receptacle

# Application

**High Ampacity Connections** 

#### Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

#### General

Style

Catalog Number **HBLFRSBL** Color Blue **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Panel Mount Receptacle Item Type Material Elastomer / Elastomeric Threaded Thru-Hole Material - Mounting Hardware Number Of Poles 1-Pole Series Series 16 Specifications

Base Compound Thermoplastic Elastomer

• Contact Material - Brass

• Mounting Hole - 4x Ø .20"

 Retaining Screw Material -Nylon

 Termination - 1/2-13 UNC-2A Threaded Stud

Stud Type, Female



Type Receptacle UPC 783585112664

# **Dimensions**

Display Size Standard Sized Product

# **Electrical Ratings**

Amperage Rating 400 A
Connectivity Stud Type
Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC
Wattage 240000

### **Conductor Related**

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

#### **Certifications And Compliance**

Industry Standard(s)

• National Electric Code
(NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

#### Logistics

Carton Quantity 25
Pallet Quantity 1575

#### **Product Assets**

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices



©2025 Hubbell Incorporated. All rights reserved BRY-HBLFRSBL-SPEC-EN | REV 1/2025