BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes

By Bryant Catalog # HBLFRSCBN

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, Brown

Features

- · Industrial Grade
- Female Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number
Color
EU RoHS Indicator
Environmental Conditions

Item Type Material

Material - Mounting Hardware

Number Of Poles

Series

Specifications

HBLFRSCBN Brown

Yes

Indoor Dry Unless Protected By Additional Means

Panel Mount Receptacle Elastomer / Elastomeric Threaded Thru-Hole

1-Pole Series 16

• Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material -Nylon
- Termination 1/2-13 UNC-2A Threaded Stud



Style Stud Type, Threaded Hole

Mounting, Female Receptacle

Type Receptacle UPC 783585093659

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A
Connectivity Stud Type
Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC
Wattage 240000

Conductor Related

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog



©2024 Hubbell Incorporated. All rights reserved BRY-HBLFRSCBN-SPEC-EN | REV 10/2024