BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded **Mounting Holes**

By Bryant Catalog # HBLFRSCR

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, Red

Features

- Industrial Grade
- Female Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number **HBLFRSCR** Color Red **EU RoHS Indicator Environmental Conditions** Additional Means Item Type Panel Mount Receptacle

Material Material - Mounting Hardware

Number Of Poles

Series

Specifications

Indoor Dry Unless Protected By Elastomer / Elastomeric Threaded Thru-Hole

1-Pole Series 16

- Base Compound -Thermoplastic Elastomer
- Contact Material Brass
- Mounting Hole 4x Ø .20"
- · Retaining Screw Material -
- Termination 1/2-13 UNC-2A Threaded Stud



Style Stud Type, Threaded Hole

> Mounting, Female Receptacle

Туре UPC 783585093604

Dimensions

Standard Sized Product Display Size

Electrical Ratings

400 A Amperage Rating Connectivity Stud Type Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase Voltage Rating Description 600V AC/DC Wattage 240000

Conductor Related

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)

• National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024



©2024 Hubbell Incorporated. All rights reserved BRY-HBLFRSCR-SPEC-EN | REV 10/2024