## **BRYANT®**

# Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes

By Bryant Catalog # HBLFRSCW

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, White

## **Features**

- · Industrial Grade
- Female Receptacle
- 300/400A 600V AC/DC

### **Application**

**High Ampacity Connections** 

## Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

## General

Item Type

Catalog Number HBLFRSCW

Color White

EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unle

Material Mounting Hardware

Number Of Poles Series

Specifications

Yes
Indoor Dry Unless Protected By
Additional Means
Panel Mount Receptacle
Elastomer / Elastomeric
Threaded Thru-Hole
1-Pole

• Base Compound -Thermoplastic Elastomer

Series 16

- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material -Nylon
- Termination 1/2-13 UNC-2A Threaded Stud



Style Stud Type, Threaded Hole

Mounting, Female

Type Receptacle UPC 783585093598

**Dimensions** 

Display Size Standard Sized Product

## **Electrical Ratings**

Amperage Rating 400 A
Connectivity Stud Type
Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC
Wattage 240000

#### **Conductor Related**

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

### **Certifications And Compliance**

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

## Logistics

Carton Quantity 25 Pallet Quantity 1575

## **Product Assets**

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024



©2024 Hubbell Incorporated. All rights reserved BRY-HBLFRSCW-SPEC-EN | REV 10/2024