
BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, **Threaded Mounting Holes**

By Bryant Catalog # HBLFRSCY





Application

High Ampacity Connections

General

Color

Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Performance

Yellow

Jaune

Indoor Dry Unless Protected By Additional Means Panel Mount Receptacle Elastomer / Elastomeric Threaded Thru-Hole

- Electrical Amperage Rating - 400A Maximum
- Electrical Voltage Ratings - 600V AC Maximum
- 250V DC Maximum
- · Environmental -Flammability - HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification - Ratings are a permanent part of device
- Mechanical Terminal Accommodation - #4 to 4/0 AWG

Series 16

Series

Style Stud Type, Threaded Hole

Mounting, Female

Receptacle Type UPC 783585093635

Dimensions

Display Size Standard Sized Product

Electrical Ratings

400 A Amperage Rating Connectivity Stud Type Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase Voltage Rating Description 600V AC/DC 240000 Wattage

Conductor Related

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

Certifications and Compliance

Industry Standard(s)

- · National Electric Code (NEC), ANSI/NFPA 70
- UL and cUL Listed
- UL Enclosure Types 3R, 4X, 12

Non-NEMA Nema Rating

Logistics

Carton Quantity 25

Product Assets

Catalog Page - Bryant L-5 Catalog page Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices

