BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A, 600V AC/DC, Single Conductor, Set Screw, White

By Bryant Catalog # HBLFRW

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A, 600V AC/DC, Single Conductor, Set Screw, White

Features

- Industrial Grade
- Female Receptacle
- 300/400A

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number **HBLFRW** Color White **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Panel Mount Receptacle Item Type Material Elastomer / Elastomeric Threaded Thru-Hole Material - Mounting Hardware

Number Of Poles 1-Pole Series Series 16

Specifications

• Base Compound -Thermoplastic Elastomer

- · Contact Material Brass
- Mounting Hole 4x #10-32
- Retaining Screw Material -
- Termination (2) 7/32 Socket Head Set Screws Double Set Screw Female



Type Receptacle **UPC** 783585112732

Dimensions

Display Size Standard Sized Product

Electrical Ratings

400 A Amperage Rating Connectivity Double Set Screw Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase Voltage Rating Description 600V AC/DC

Conductor Related

Wattage

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) · National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

240000

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices

Style



©2025 Hubbell Incorporated. All rights reserved BRY-HBLFRW-SPEC-EN | REV 1/2025