BRYANT®

Heavy Duty Products, Single Pole **Devices, Industrial Grade, Male Bus** Receptacle, 300/400A 600V AC/DC, Single Conductor, Brown

By Bryant Catalog # HBLMRBBN

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Brown

Application

High Ampacity Connections

General

			-	
	Color	• Brown	Amperage Rating	400
		Marron	Connectivity	Scre
	Environmental Conditions	Indoor Dry Unless Protected	Current / Amperage Rating Current Rating	400 400
	Item Type	Flanged Single	Phase	Sing
	Material	Thermoplastic	Voltage Rating Description	600
	Material - Mounting Hardware	Screw Mounting	Wattage	240
	Number Of Poles Performance	 Electrical - Amperage 	Conductor Related	
		Rating - 400A Maximum	Wire Size	#4 .
		 Electrical - Voltage Ratings 600V AC Maximum 	Certifications and Complian	nce
		• 250V DC Maximum	Industry Standard(s)	• 1
		 Environmental - Flammability - HB per UL94 or CSA 22.2. 0.17 		• l
		 Mechanical - Product Identification - Ratings are a permanent part of device 	Nema Rating	1 Nor
			Logistics	
		Accommodation - #4 to 4/0 AWG	Carton Quantity	25
	Series	Series 16	Product Assets	
	Style	Bus Bar Mount Male	Catalog Page - Bryant L-6 Cata	alog p
	Туре		Catalogs - Bryant Full Line Catalog	
	UPC	783585192604	Literature - Single Pole Devices	5



Dimensions

Display Size

Electrical Ratings

mperage Rating	400 A			
onnectivity	Screw Terminals			
urrent / Amperage Rating	400 A			
urrent Rating	400 A			
lase	Single Phase			
oltage Rating Description	600V AC/DC			
attage	240000			
onductor Related				
ire Size	#4 AWG to #4/0 AWG			
ertifications and Compliance				
dustry Standard(s)	 National Electric Code (NEC), ANSI/NFPA 70 			
	UL and cUL Listed			
	• UL Enclosure Types 3R, 4X, 12			
ema Rating	Non-NEMA			
ogistics				
arton Quantity	25			
oduct Assets				
talog Pago - Bryant L-6 Catalog pago				

Standard Sized Product

page

