BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Yellow

By Bryant Catalog # HBLMRBY

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Bus Receptacle, 300/400A 600V AC/DC, Single Conductor, Yellow

Features

- Industrial Grade
- Male Bus Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number HBLMRBY
Color Yellow
EU RoHS Indicator No
Environmental Conditions Indoor Dry Unless Protected By

Additional Means
Item Type Flanged Single
Material Thermoplastic
Material - Mounting Hardware Screw Mounting

Number Of Poles 1-Pole Series Series 16

Specifications

• Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x #10-32
- Retaining Screw Material -Nylon
- Termination 5/16-18 UNC-2B Threaded Hole

Style Bus Bar Mount Male



Type Receptacle UPC 783585192628

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A

Connectivity Screw Terminals

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC

Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70

UL and cUL Listed

UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalog Page - WDK H-7 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices Specifications - HBLMRBY

