BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Orange

By Bryant Catalog # HBLMRO

Heavy Duty Single Pole Industrial Grade Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw



- · Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number HBLMRO
Color Orange
EU RoHS Indicator Yes
Environmental Conditions Indoor Dr

Environmental Conditions Indoor Dry Unless Protected By

Additional Means
Item Type Flanged Single
Material Thermoplastic
Material - Mounting Hardware Screw Mounting

Number Of Poles 1-Pole Series Series 16

> Base Compound -Thermoplastic Elastomer

• Contact Material - Brass

Mounting Hole - 4x #10-32

 Retaining Screw Material -Nylon

Termination - (2) 7/32
 Socket Head Set Screws

Double Set Screw Male



Type Receptacle UPC 783585112978

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A

Connectivity Screw Terminals

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC

Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70

UL and cUL Listed

UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Single Pole Devices Specifications - HBLMRO

Style

Specifications

