BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue



By Bryant Catalog # HBLMRSBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue

Features

- Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent
 part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Series

Specifications

Catalog Number Color EU RoHS Indicator Environmental Conditions Item Type Material Material - Mounting Hardware Number Of Poles HBLMRSBL Blue Yes Indoor Dry Unless Protected By Additional Means Flanged Single Thermoplastic Screw Mounting 1-Pole Series 16

- Base Compound Thermoplastic Elastomer
- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material Nylon
- Termination 1/2-13 UNC-2A Threaded Stud

Style

Type UPC Stud Type, Through Hole Mounting, Male Receptacle 783585113005

Dimensions

Display Size

Standard Sized Product

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Phase Voltage Rating Description Wattage

Conductor Related

#4 AWG to #4/0 AWG

- Certifications And Compliance Industry Standard(s) • Natio
 - National Electric Code
 (NEC), ANSI/NFPA 70
 - UL and cUL Listed
 - UL Enclosure Types 3R, 4X, 12
 Non-NEMA

Nema Rating

Logistics

Carton Quantity	25
Pallet Quantity	1575

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog

400 A 400 A Single Phase 600V AC/DC 240000

Screw Terminals

400 A



©2025 Hubbell Incorporated. All rights reserved BRY-HBLMRSBL-SPEC-EN | REV 1/2025