BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue



By Bryant Catalog # HBLMRSBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue

Features

- Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent
 part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number Color EU RoHS Indicator Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Series Specifications

- HBLMRSBL Blue Yes Indoor Dry Unless Protected By Additional Means Flanged Single Thermoplastic Screw Mounting 1-Pole Series 16 • Base Compound -
- Thermoplastic ElastomerContact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material Nylon
- Termination 1/2-13 UNC-2A Threaded Stud

Style Type

UPC

Dimensions Display Size

Standard Sized Product

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Phase Voltage Rating Description Wattage

Conductor Related

Wire Size

Certifications And Compliance

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

• UL and cUL Listed

#4 AWG to #4/0 AWG

Stud Type, Through Hole

Mounting, Male

783585113005

Receptacle

400 A

400 A

400 A

240000

Screw Terminals

Single Phase

600V AC/DC

 UL Enclosure Types 3R, 4X, 12
 Non-NEMA

Nema Rating

Logistics

| Carton Quantity | 25 |
|-----------------|------|
| Pallet Quantity | 1575 |

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog



©2024 Hubbell Incorporated. All rights reserved BRY-HBLMRSBL-SPEC-EN | REV 10/2024