BRYANT®

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes



By Bryant Catalog # HBLMRSCO

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, Orange

Features

- Industrial Grade
- Male Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent
 part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number Color EU RoHS Indicator Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Series Specifications

- HBLMRSCO Orange Yes Indoor Dry Unless Protected By Additional Means Flanged Single Thermoplastic Screw Mounting 1-Pole Series 16 • Base Compound -
- Base compound -Thermoplastic Elastomer
 Contact Material - Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material Nylon
- Termination 1/2-13 UNC-2A Threaded Stud

Style

Type UPC

Dimensions Display Size

Standard Sized Product

Screw Terminals

Single Phase

600V AC/DC

400 A

400 A

400 A

240000

Mounting, Male

783585093567

Receptacle

Stud Type, Threaded Hole

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Phase Voltage Rating Description Wattage

Conductor Related

Wire Size

Certifications And Compliance

Industry Standard(s)

 National Electric Code (NEC), ANSI/NFPA 70

#4 AWG to #4/0 AWG

- UL and cUL Listed
- UL Enclosure Types 3R, 4X, 12
 Non-NEMA

Nema Rating

Logistics

Carton Quantity	25
Pallet Quantity	1575

Product Assets

Catalog Page - WDK H-6 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog



©2024 Hubbell Incorporated. All rights reserved BRY-HBLMRSCO-SPEC-EN | REV 10/2024