BRYANT®

Combination Devices, Residential Grade, 1) Three Way Toggle, 1) Single Receptacle, 15A 120V AC, Self Grounding, Side Wired

By Bryant Catalog # RC308I

One Three Way Toggle One Single Receptacle Combination Device, Residential 15A 120V AC, Self Grounding, Side Wired

Features

- Quiet snap action mechanism
- Self-grounding staple is standard
- Elongated strap with continuous plaster ears

Application

Residential

General

Action	Snap Switch
Actuator	Toggle
Contact Configuration	Two Position
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Traditional Switch and Receptacle Combo Devices
Material - Mounting Hardware	Mounting Screws
Number Of Poles	1) Three Way
Operating Cycles	30,000 Minimum
Operating Temperature	Max Continuous- 60 Degrees C, Minimum20 Without Impact
Performance	Environmental - Operating temperature20°C to 60°C
UPC	883778109843
Dimensions	
Display Size	Standard Size



Electrical Ratings

Amperage Rating	15 A	
Connectivity	Side Wired	
Contact Rating	15A	
Current / Amperage Rating	15 A	
Current Rating	15 A	
Voltage Rating	120 VAC	
Voltage Rating Description	120 VAC	
Wattage	1800	

Certifications and Compliance

Industry Standard(s)	UL Listed
Logistics	
Carton Quantity	10

Product Assets

Catalog Page - Bryant E-7 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

RC309W - Switches and Lighting Controls, Combination
Devices, Residential Grade, 1) Three Way Toggle, 1) Pilot Light,
15A 120V AC, Self Grounding, Side Wired
RC103W - Combination Devices, Residential Grade, 1) Single
Pole Toggle, 1) Three Way Toggle, 15A 120V AC, Self
Grounding, Side Wired
RC308TR - Combination Devices, Residential Grade, 1) Three
Way Toggle, 1) Single Tamper Resistant Receptacle, 15A 120V
AC, Self Grounding, Side Wired
RC103 - Combination Devices, Residential Grade, 1) Single Pole
Toggle, 1) Three Way Toggle, 15A 120V AC, Self Grounding,
Side Wired, Brown

RC309AL - COMBO, 15A 3W TOG, PILOT/ILLUM, AL

