BRYANT®

Combination Devices, Residential Grade, 1) Three Way Toggle, 1) Single Tamper Resistant Receptacle, 15A 12OV AC, Self Grounding, Side Wired

By Bryant Catalog # RC308TR

One Three Way Toggle One Single Tamper Resistant Receptacle Combination Device, Residential 15A 120V AC, Self Grounding, Side Wired



- · Quiet snap action mechanism
- · Self-grounding staple is standard
- Elongated strap with continuous plaster ears

Application

Residential

General

Action Snap Switch
Actuator Toggle
Contact Configuration Two Position

Environmental Conditions Indoor Dry Unless Protected

By Additional Means

Item Type Traditional Switch and Receptacle Combo Devices

Material - Mounting Hardware Mounting Screws
Number Of Poles 1) Three Way

Operating Cycles 30,000 Minimum

Operating Temperature Max Continuous- 60 Degrees C, Minimum- -20 Without

Impact

Performance Environmental - Operating temperature - -20°C to 60°C

UPC 883778302299

Dimensions

Display Size Standard Size



Electrical Ratings

Amperage Rating 15 A Connectivity Side Wired Contact Rating 15A Current / Amperage Rating 15 A **Current Rating** 15 A Voltage Rating 120 VAC 120 VAC Voltage Rating Description Wattage 1800

Certifications and Compliance

Industry Standard(s) UL Listed

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant E-7 Catalog page Catalogs - Bryant Full Line Catalog

Related Products

RC303 - Switches and Lighting Controls, Combination Devices, Residential Grade, 2) Three Way Toggles, 15A 120V AC, Self Grounding, Side Wired, Brown

RC103 - Combination Devices, Residential Grade, 1) Single Pole Toggle, 1) Three Way Toggle, 15A 12OV AC, Self Grounding, Side Wired, Brown

P26I - Wallplate, 1-Gang, 1) Decorator, Ivory

RC303W - Switches and Lighting Controls, Combination Devices, Residential Grade, 2) Three Way Toggles, Self Grounding, 15A 120V AC, Side Wired, White

RC308I - Combination Devices, Residential Grade, 1) Three Way Toggle, 1) Single Receptacle, 15A 120V AC, Self

Grounding, Side Wired

